



NEW PRODUCTS

LED PRODUCT AND APPLICATION PROVIDER









- 1. Customer Satisfaction is the eternal pursual of our Company.
- 2. Quality and improvement our motto.
- 3. Survive by quality, development & efficiency by our management.\
- 4. Attention to every detail and efficiency in each hour are the key to a great working day.



Contents

LED DOWN SERIES1-7
LED TUBE LIGHT SERIES8-9
LED MIRROR LIGHT SERIES10-11
LED STRIP LIGHTS SERIES12-14
COB SERIES15-17
LED SLIM PANEL SERIES18-19
LED SURFACE LIGHTS SERIES20
LED DOWN LIGHT SERIES21
I FD STRIP DRIVER22





Product features:

- 1. The unique and artistic design with stories.
- 2. Efficacy 90-100lm/w and build-in import epistar led chip, high brightness and low energy consumption.
- 3. Designed with up to 50,000 hour expected useful life, 10 times than ordinary fluorescent lamp.
- 4. Wide range of temperature can provide almost any color
- 5. The LED lamp lights up instantly to full brightness, no noise, no light flicker or noise.
- 6. Eco-friendly, no UV or IR radiation, lead or mercury, or other hazardous substances.
- 7. This light is ideal for a wide range of application, suitable for home, office, school, showcase, gallery hall, boutique, meeting room and other places.











GP-012

Voltage: 85-260V 50/60Hz

CRI: Ra70


Life: 30000hrs

Power: 12W

Lumens: 1050-1200LM LED QTY:72PCS(2835)

Outer Size: 125mm

Cut Size **Φ** 115mm













GP-018

Voltage: 85-260V 50/60Hz

CRI: Ra70

Life: 30000hrs


Power: 18W

Lumens: 1650-1800LM LED QTY:108PCS(2835)



Outer Size: 155mm

Cut Size **Φ** 147mm













GP-024

Voltage: 85-260V 50/60Hz

CRI: Ra70

Life: 30000hrs


Power: 24W

Lumens: 2150-2400LM LED QTY:144PCS(2835)



Outer Size: 175mm

Cut Size **Φ** 167mm













GP-012-SQ

Voltage: 85-260V 50/60Hz

CRI: Ra70

Life: 30000hrs


Power: 12W

Lumens: 1050-1200LM

LED QTY:72PCS(2835)



Cut Size **O**uter Size :110 x 110 mm















GP-018-SQ

Voltage: 85-260V 50/60Hz

CRI: Ra70


Life: 30000hrs

Power: 18W

Lumens: 1650-1800LM

LED QTY:108PCS(2835)

















GP-024-SQ

Voltage: 85-260V 50/60Hz

CRI: Ra70


Life: 30000hrs


Power: 24W

Lumens: 2150-2400LM LED QTY:144PCS(2835)



Cut Size **d** Outer Size :170 x 170 mm







LED TUBE LIGHT SERIES




Product features:

- 1. Aluminium extrusion: high quality die-casting aluminium housing, excellent heat dissipation
- 2. Housing: nice flowing lines. milky white PC cover, provides perfect light distribution.
- 3. Build-in Epistar chip: Taiwan import epistar ed chip, SMD technology, reliable long operating life.
- 4. Internal driver: constant voltage and current, intelligent IC power management, stable power supply.
- 5. Installed way: equip with clip fitting, easy to install.
- 6. 113° Lighting provides a wide range of light distribution



LED TUBE LIGHT SERIES

Specifica	ition	Size	LED qty	Luminous	Effciency	Power	CRI	Input
MODEL NO	Power (W)	(mm)	(pcs)	(LM)	(LM/W)	factor	Citi	(V)
GP-T5010	10	300*21*34	30	900-1000		0.6	70	85-260
GP-T5016	16	600*21*34	60	1440-1600	90-100	0.9	70	85-260
GP-T5024	24	1200*21*34	120	2100-2400		0.9	70	85-260





LED MIRROR LIGHT SERIES




Application:

Widely used in Residential, Hotel, Restaurant, Cottage, Office, Market, Resting Room, Dining Room and Entertainment Center etc.




LED MIRROR LIGHT SERIES







Aluminium housing, 80 degree adjustable.





LED STRIP LIGHTS SERIES



Feature:

- 1. Can be dimmable with dimmer controller
- 2. Ultra Bright LED's
- 3. Long life span
- 4. Flexible, convenient for design and motif
- 5. Energy-saving and eco-friendly
- 6. UV & Water proof PVC material
- 7. IP20-IP65 wide application for indoors & outdoors



LED STRIP LIGHTS SERIES



Model No.: GP-LS120D

Voltage: DC12V LED Type: SMD2835 LED Qty/M:120PCS PCB Width:8mm

PCB Thickness: 70µ*35µ(30Z)


Wattage: 16W/M

CRI: 80+

Luminous: 24-26lm/led

IP Grade: IP20/IP65 (slim sleeve)

Color Available: 3000K, 4500K, 6000K, Blue



Model No.: GP-LS168D

Voltage: DC12V LED Type: SMD2835 LED Qty/M:168PCS PCB Width:10mm

PCB Thickness: 70µ*35µ(30Z)


Wattage: 20W/M

CRI: 80+

Luminous: 24-26lm/led

IP Grade: IP20/ IP65 (slim sleeve)

Color Available: 3000K, 4500K, 6000K, Blue



Model No.: GP-LS240D

Voltage: DC12V LED Type: SMD2835 LED Qty/M:240PCS PCB Width:10mm

PCB Thickness: 70µ*35µ(30Z)

Wattage: 26W/M

CRI: 80+

Luminous: 24-26lm/led

IP Grade: IP20/ IP65 (slim sleeve)

Color Available: 3000K, 4500K, 6000K, Blue



LED STRIP LIGHTS SERIES



Model No.: GP-LS120D-20

Voltage: DC12V LED Type: SMD2835 LED Qty/M :120PCS PCB Width :5mm

PCB Thickness: $35\mu*35\mu(2OZ)$

Wattage: 16W/M

CRI: 80+

Luminous: 24-26lm/led

IP Grade: IP20/ IP65 (slim sleeve) Color Available: 3000K, 4500K, 6000K



Model No.: GP-LS5050

Voltage: DC12V LED Type: SMD5050 LED Qty/M:60PCSP CB Width:10mm

PCB Thickness: $70\mu*35\mu(30Z)$

Wattage: 14.4W/M

CRI: 70+

Luminous: 14-16lm/led

IP Grade: IP20/ IP65 (slim sleeve) Color Available: 2700K, 3000K, 4500K,

6000K,RGB




COB SERIES










ITEM NO.	Voltage	CRI	Power	OUTER SIZE	CUT SIZE	Lumens	Chip Brand	
			3W	Ф62*40	Ф45-55	270LM		
GP-XC001			7W	Ф85*60	Ф68-78	630LM		
	85-260V 50/60Hz		15W	Ф108*80	Ф90-105	1350LM	BridgeLux	
			30W	Ф138*120	Ф118-128	2700LM		
			40W	Ф157*113	Ф135-145	3600LM		
GP-XC001 SQ	85-260V 50/60Hz	85-260V	_	3W	62*62*40	45*45-55*55	270LM	Duide al
		$-$ D \sim O \wedge	7W	85*85*60	68*68-78*78	630LM	BridgeLux	



COB SERIES



Application:

Widely used in Residential, Hotel, Restaurant, Cottage, Office, Market, Resting Room, Dining Room and Entertainment Center etc.





COB SERIES





ITEM NO.	Voltage	CRI	Power	OUTER SIZE	CUT SIZE	Lumens	Chip Brand
GP-XC003	85-260VDC	Ra80	12W	Ф92*85	Ф70	950-1050LM	CREE


Installation:













LED SLIM PANEL SERIES



Application:


LED Ceiling Light has simple and beautiful appearance, can be applied for decorative application and lighting application.

- 1. Wall, Ceiling, Platfond, Sprung Proof, Integrated Ceiling, Grille Ceiling.
- 2. Kitchen, Office, Hotel, Hospital, Cinema, Market, Shop, Shower Room, Corridor, Lift, Etc.
- 3. Car, Showroom, Bar, Gallery, Museum.



LED SLIM PANEL SERIES






ITEM NO.	Voltage	CRI	Power	OUTER SIZE	CUT SIZE	Lumens(LM)	Chip Brand
GP-SL008	85V-265V	>70	8W	Ф120mm	100mm	600-650	
GP-SL015	85V-265V	>70	15W	Ф175mm	150mm	1300-1400	
GP-SL022	85V-265V	>70	22W	Ф225mm	200mm	1900-2000	Sanan
GP-SL008 SQ	85V-265V	>70	8W	120 x 120mm	100 x 100mm	600-650	Sallali
GP-SL015 SQ	85V-265V	>70	15W	175 x 175mm	150 x 150mm	1300-1400	
GP-SL022 SQ	85V-265V	>70	22W	225 x 225mm	200 x 200mm	1900-2000	



LED SERFAS LIGHTS SERIES



ITEM NO.	Voltage	CRI	Power	OUTER SIZE	Lumens(LM)	Chip Brand
GP-SF008	85V-265V	>70	8W	Ф120mm	600-650	
GP-SF015	85V-265V	>70	15W	Φ175mm	1300-1400	
GP-SF022	85V-265V	>70	22W	Ф225mm	1900-2000	Sanan
GP-SF008 SQ	85V-265V	>70	8W	120 x 120mm	600-650	
GP-SF015 SQ	85V-265V	>70	15W	175 x 175mm	1300-1400	
GP-SF022 SQ	85V-265V	>70	22W	225 x 225mm	1900-2000	



LED DOWN LIGHT SERIES



ITEM NO.	LED QTY	Voltage	CRI	Power	OUTER SIZE	CUT SIZE	Lumens(LM)	Chip Brand
GP-DS016	80PCS	85V-265V	>70	16W	Ф120mm	Ф105mm	1600	
GP-DS024	120PCS	85V-265V	>70	24W	Ф170mm	Ф155mm	2200	
GP-DS032	160PCS	85V-265V	>70	32W	Ф225mm	Ф205mm	3200	Sanan
GP-DS016 SQ	80PCS	85V-265V	> 70	16W	120*120mm	105*105mm	1600	Sallali
GP-DS024SQ	120PCS	85V-265V	> 70	24W	170*170mm	155*155mm	2200	
GP-DS032 SQ	160PCS	85V-265V	> 70	32W	225*225mm	205*205mm	3200	



LED STRIP DRIVER









ITEM NO.	Ampere	Volt	Power	Voltage	IP
GP-12060-N	5A	DC12V	60W	AC170V-250V	IP20
GP-12080-N	6.5A	DC12V	80W	AC170V-250V	IP20
GP-12100-N	8.3A	DC12V	100W	AC170V-250V	IP20
GP-12120-N	10A	DC12V	120W	AC170V-250V	IP20
GP-12150-N	12.5A	DC12V	150W	AC170V-250V	IP20
GP-12200-N	16.6A	DC12V	200W	AC170V-250V	IP20
GP-12250-N	20.8A	DC12V	250W	AC170V-250V	IP20
GP-12300-N	25A	DC12V	300W	AC170V-250V	IP20
GP-12350-N	29.2A	DC12V	350W	AC170V-250V	IP20
GP-12400-N	33.3A	DC12V	400W	AC170V-250V	IP20









MAHAKALI

Light house

Address

Room No. 24, 1st Floor, Jay Mahal Bldg., Kitchen Garden Lane, Lohar Chawl, Mumbai - 400 002. Maharashtra, India. Mob.: +91 9892133177 / 9867302711 Tel.: 022 3956 7946 *7946

E-mail: mahakalilighthouse@gmail.com / info@great-plus.com www.great-plus.com

